

SAFETY DATA SHEET



Issuing Date 28-May-2020

Revision date 28-May-2020

Revision Number 1

1. Identification

Product identifier

Product Name MG 400/405

Other means of identification

Product Code(s) WA00002

Synonyms MG 400/405 electrode

Recommended use of the chemical and restrictions on use

Recommended use Covered Electrode for Shielded Metal Arc Welding (SMAW)

Restrictions on use

Details of the supplier of the safety data sheet

Supplier Address

MG Welding, N94W14355 Garwin Mace Dr., Menomonee Falls, WI 53051, USA

Manufacturer Address

MG Welding, N94W14355 Garwin Mace Dr., Menomonee Falls, WI 53051, USA

Emergency telephone number

Company Phone Number 1-262-532-4677

Emergency Telephone Chemtrec 1-800-424-9300

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Skin corrosion/irritation	Category 1 Sub-category A
Serious eye damage/eye irritation	Category 1

Hazards not otherwise classified (HNOC)

Not applicable

Label elements

Danger

Hazard statements

Harmful if swallowed

Causes severe skin burns and eye damage



Appearance Coated electrode

Physical state Solid

Odor Odorless

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product
 Do not breathe dusts or mists
 Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

Immediately call a POISON CENTER or doctor
 Specific treatment (see on this label)
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 Immediately call a POISON CENTER or doctor
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower
 Wash contaminated clothing before reuse
 IF INHALED: Remove person to fresh air and keep comfortable for breathing
 Immediately call a POISON CENTER or doctor
 IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell
 Rinse mouth
 Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

When this product is used in a welding process, the hazards are mostly from electric shock, heat, radiation, fumes and gases. Electric shock can kill. Arc rays, spatter, and melting metals can severely injure eyes and burn skin. Welding arc and sparks can cause fire

Fumes and gases can be dangerous to your health. Certain medical studies have suggested that nervous system and/or lung damage can result from overexposure to welding fumes and gases

The welding fumes and gases produced from welding rod, coating flux, and base metal in a welding process may contain manganese and manganese compounds, nickel and nickel compounds, chromium (VI) and chromium compound, carbon dioxide, carbon monoxide, nitrogen dioxide, and ozone

Overexposure to manganese and its compounds may cause metal fume fever and affect the central nervous system. Prolonged inhalation of nickel and chromium (VI) compounds above safe exposure limits can cause cancer

Unknown acute toxicity 100.7828 % of the mixture consists of ingredient(s) of unknown toxicity
 58.7648 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
 84.6028 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
 100.7828 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
 100.7828 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
 100.7828 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Synonyms MG 400/405 electrode.

Chemical name	CAS No.	Weight-%	Trade secret
Aluminum	7429-90-5	30-60	*
Potassium hydroxide	1310-58-3	3-7	*
Silicon	7440-21-3	1-5	*
Potassium Tetrafluoroaluminate	14484-69-6	1-5	*
Magnesium Fluoride Powder	7783-40-6	0.5-1.5	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Inhalation	Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get immediate medical advice/attention.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get immediate medical advice/attention.
Ingestion	Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Symptoms Burning sensation.

Indication of any immediate medical attention and special treatment needed

Note to physicians Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure.

5. Fire-fighting measures

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	CAUTION: Use of water spray when fighting fire may be inefficient.
Specific hazards arising from the chemical	The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors.
Explosion data	
Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.
Special protective equipment for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Attention! Corrosive material. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.
Other information	Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment	Prevent further leakage or spillage if safe to do so.
Methods for cleaning up	Pick up and transfer to properly labeled containers.

7. Handling and storage

Precautions for safe handling

Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment such as an air supplied respirator. Handle product only in closed system or provide appropriate exhaust ventilation. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.
--------------------------------	---

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Protect from moisture. Store locked up. Store away from other materials.
---------------------------	--

8. Exposure controls/personal protection

Control parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Aluminum 7429-90-5	TWA: 1 mg/m ³ respirable particulate matter	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Potassium hydroxide	Ceiling: 2 mg/m ³	(vacated) Ceiling: 2 mg/m ³	Ceiling: 2 mg/m ³

1310-58-3 Silicon 7440-21-3	No data available	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Potassium Tetrafluoroaluminate 14484-69-6	TWA: 2.5 mg/m ³ F	TWA: 2.5 mg/m ³ F (vacated) TWA: 2.5 mg/m ³	IDLH: 250 mg/m ³ F TWA: 2.5 mg/m ³ F
Magnesium Fluoride Powder 7783-40-6	TWA: 2.5 mg/m ³ F	TWA: 2.5 mg/m ³ F (vacated) TWA: 2.5 mg/m ³	IDLH: 250 mg/m ³ F TWA: 2.5 mg/m ³ F

Appropriate engineering controls

Engineering controls Showers
 Eyewash stations
 Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Face protection shield.

Hand protection Wear suitable gloves. Impervious gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties**Information on basic physical and chemical properties**

Physical state Solid
Appearance Coated electrode
Color white
Odor Odorless
Odor threshold

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	None known
Melting point / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash point	No data available	None known
Evaporation rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	No data available	None known
Water solubility	No data available	None known

Solubility in other solvents	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

Other information

Explosive properties

Oxidizing properties

VOC Content (%)

10. Stability and reactivity

Reactivity	.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	None under normal processing.
Conditions to avoid	Exposure to air or moisture over prolonged periods.
Incompatible materials	Acids. Bases. Oxidizing agent.
Hazardous decomposition products	None known based on information supplied.

11. Toxicological information**Information on likely routes of exposure****Product Information**

Inhalation	Specific test data for the substance or mixture is not available. Corrosive by inhalation. (based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal.
Eye contact	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Corrosive to the eyes and may cause severe damage including blindness. Causes serious eye damage. May cause irreversible damage to eyes.
Skin contact	Specific test data for the substance or mixture is not available. May cause irritation.
Ingestion	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	Redness. Burning. May cause blindness. Coughing and/ or wheezing.
-----------------	---

Acute toxicity**Numerical measures of toxicity**

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 1,654.70 mg/kg
ATEmix (dermal) 9,525.70 mg/kg

Unknown acute toxicity 100.7828 % of the mixture consists of ingredient(s) of unknown toxicity
58.7648 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
84.6028 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
100.7828 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
100.7828 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
100.7828 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Potassium hydroxide 1310-58-3	= 284 mg/kg (Rat)	-	-
Silicon 7440-21-3	= 3160 mg/kg (Rat)	-	-
Magnesium Fluoride Powder 7783-40-6	= 2330 mg/kg (Rat)	-	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes burns. Risk of serious damage to eyes.

Respiratory or skin sensitization .

Germ cell mutagenicity .

Carcinogenicity .

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Potassium Tetrafluoroaluminate 14484-69-6	-	Group 3	-	-
Magnesium Fluoride Powder 7783-40-6	-	Group 3	-	-

Legend

IARC (International Agency for Research on Cancer)
Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive toxicity .

STOT - single exposure .

STOT - repeated exposure .

Target organ effects Respiratory system, Eyes, Skin.

Aspiration hazard .

Other adverse effects .

Interactive effects .

12. Ecological information

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Potassium hydroxide 1310-58-3	-	LC50: =80mg/L (96h, Gambusia affinis)	-	-

Persistence and degradability

Bioaccumulation

There is no data for this product.

Component Information

Chemical name	Partition coefficient
Potassium hydroxide 1310-58-3	0.83

Other adverse effects

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products

Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging

Do not reuse empty containers.

California Hazardous Waste Status

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste Status
Aluminum 7429-90-5	Ignitable powder
Potassium hydroxide 1310-58-3	Toxic Corrosive

14. Transport information

DOT Not regulated

TDG Not regulated

MEX Not regulated

ICAO (air) Not regulated

IATA Not regulated

IMDG Not regulated

RID Not regulated

ADR Not regulated

ADN Not regulated

15. Regulatory information

International Inventories

TSCA Contact supplier for inventory compliance status.
DSL/NDSL Contact supplier for inventory compliance status.
EINECS/ELINCS Contact supplier for inventory compliance status.
ENCS Contact supplier for inventory compliance status.
IECSC Contact supplier for inventory compliance status.
KECL Contact supplier for inventory compliance status.
PICCS Contact supplier for inventory compliance status.
AICS Contact supplier for inventory compliance status.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Potassium hydroxide 1310-58-3	1000 lb	-	-	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs
Potassium hydroxide 1310-58-3	1000 lb	-

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

US State Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Aluminum 7429-90-5	X	X	X
Potassium hydroxide 1310-58-3	X	X	X
Silicon 7440-21-3	X	X	X
Potassium Tetrafluoroaluminate 14484-69-6	X	-	-
Magnesium Fluoride Powder 7783-40-6	X	-	-

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA	Health hazards 3	Flammability 0	Instability 0	Physical and chemical properties -
HMIS	Health hazards 3	Flammability 0	Physical hazards 0	Personal protection X

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation

Key literature references and sources for data used to compile the SDS

- Agency for Toxic Substances and Disease Registry (ATSDR)
- U.S. Environmental Protection Agency ChemView Database
- European Food Safety Authority (EFSA)
- EPA (Environmental Protection Agency)
- Acute Exposure Guideline Level(s) (AEGl(s))
- U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
- U.S. Environmental Protection Agency High Production Volume Chemicals
- Food Research Journal
- Hazardous Substance Database
- International Uniform Chemical Information Database (IUCLID)
- Japan GHS Classification
- Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
- NIOSH (National Institute for Occupational Safety and Health)
- National Library of Medicine's ChemID Plus (NLM CIP)
- National Library of Medicine's PubMed database (NLM PUBMED)
- National Toxicology Program (NTP)
- New Zealand's Chemical Classification and Information Database (CCID)
- Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
- Organization for Economic Co-operation and Development High Production Volume Chemicals Program
- Organization for Economic Co-operation and Development Screening Information Data Set
- RTECS (Registry of Toxic Effects of Chemical Substances)
- World Health Organization

Issuing Date 28-May-2020

Revision date 28-May-2020

Revision Note .

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet